

# MV CURRENT TRANSFORMERS, OUTDOOR OIL INSULATED

Company: \_\_\_\_\_ Date: \_\_\_\_\_ Telephone: \_\_\_\_\_  
Contact Name: \_\_\_\_\_ FAX: \_\_\_\_\_  
Address: \_\_\_\_\_ City: \_\_\_\_\_ State \_\_\_\_\_ ZIP \_\_\_\_\_  
Application: \_\_\_\_\_ Customer P/N: \_\_\_\_\_  
Quote on: 1 10 25 50 100 500 1000 5000 10000 Estimated Annual Usage: \_\_\_\_\_  
Prototype Needed (when): \_\_\_\_\_ Production Planned (when): \_\_\_\_\_

Current Ratio: : \_\_\_\_\_

Accuracy Class: \_\_\_\_\_ Burden: \_\_\_\_\_ VA Frequency: \_\_\_\_\_

Dimensional limitation (if any, attach sketch if available) :

System Voltage: = \_\_\_\_\_ Volts CT Type: [ ] Metering [ ] Relay [ ] Other \_\_\_\_\_  
Vk: \_\_\_\_\_  
Imag: \_\_\_\_\_ mA@ Vk \_\_\_\_\_

Standard: [ ] IS 2705, [ ] IEC 60044, [ ] ANSI C57.13, [ ] Other \_\_\_\_\_

Type: [ ] Dead tank type [ ] Live tank type

Specifications for the tank housing and its outer covering:

Secondary Terminal:

- [ ] Nylon encapsulated brass Terminals (Type)
- [ ] Resin encapsulated brass Terminals (Type)

Primary Terminal (for wound type):

- [ ] Copper bar
- [ ] Brass/Copper studs
- [ ] Brass/Copper lugs

Mounting Requirement: (Please specify)

## Please specify the following information if available

Turns Ratio : \_\_\_\_\_ (if different than current ratio)

Continuous Thermal Current = \_\_\_\_\_ times at \_\_\_\_\_ temperature or R.F. = \_\_\_\_\_

Short time Thermal Current  $I_{th}$  = \_\_\_\_\_ kA for \_\_\_\_\_ Seconds

Peak Dynamic Current =  $I_{th}$  x \_\_\_\_\_ times

BIL : \_\_\_\_\_ kV

Application / Intended Use :

Special requirements Viz for Label, color, unusual ambient conditions, unusual exposure climate (attach sheets)

Attach sketch / drawing if available